


Core count	12
Rated Voltage/Current	3A/60V
Rated Pulse Voltage	500V
Insulation Resistance (M Ω)	≥ 100
Contact Resistance (m Ω)	≤ 5

6	Nut	PA66 UL94-V0	Black	1	-TOLERANCES- UNLESS OTHERWISE SPECIFIED	 Metabee (Chengdu) Technology Co., Ltd. Tel: +8615926241606 E-mail: Sales@metabeeai.com						
5	Sealing Ring	NBR	Black	/		UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 -120mm ± 0.30mm			PART DESCRIPTION: M16 male Connector,ASS'Y Type,shielded			
4	Center Pin	Copper Alloy	Gold Plating	12			Appd:	Jim.king	P/N: M16A-12PM-AS-S001			
3	Insulator	PA66 UL94-V0	Black	1	Check:			Date	Scale	Unit	Page	
2	Shell	Zinc Alloy	Nickel Plating	1	Draw:		Gavin	2025.03.12	Free	MM	1/1	
1	Body	Zinc Alloy	Nickel Plating	1								
NO	DESCRIPTION	MATERIAL	FINISH	QTY								