

M16 male Connector ASS'Y Type,shielded

Features:

- Threaded Coupling
- IP67 (Rating)
- Pollution Degree: 3
- Products Comply With IEC 61076-2-101 Industry 4.0 Agreement, NEMA2000 Standard



Electrical Specifications

Contacts	12
Rated Current (A)	3
Rated Voltage (AC,V)	60
Rated Pulse Voltage (AC,V)	500
Insulation Resistance (MΩ)	≥100
Contact Resistance (mΩ)	≤5

Mechanical Specifications

Mating Cycles	500 Min
Coupling Mechanism	Threaded
Interface Specification	IEC 61076-2-101



Environmental Specifications

Temperature Range	-20°C to +85°C
-------------------	----------------

Material Specifications

Shell	Zinc Alloy, Nickel Plating
Body	Zinc Alloy, Nickel Plating
Insulator	PA66 UL94-V0, Black
Contacts	Copper Alloy, Gold Plating
Sealing Ring	NBR, Black
Nut	PA66 UL94-V0, Black

Drawing



UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS
ARE:

0.5 - 8mm ± 0.20 mm
8 - 30mm ± 0.25 mm
30 - 120mm ± 0.30 mm

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.