






REV	DESCRIPTION	DATE	APPROVEN
R1.0	First issue	2025/03/12	JIM.KING



Recommended
Panel cut-out

Technical Specifications	
Coupling	Threaded Coupling
Termination	Screw
Pollution Degree	3
Mating Cycles	≥500
IP Rating	IP67 When Mated
Temperature Range	-25°C ~ +80°C

Core count	14
Rated Voltage/Current	3A/60V
Rated Pulse Voltage	500V
Insulation Resistance (MΩ)	≥100
Contact Resistance (mΩ)	≤5

					-TOLERANCES- UNLESS OTHERWISE SPECIFIED	Metabee (Chengdu) Technology Co., Ltd. Tel: +8615926241606 E-mail: Sales@metabeeai.com					
5	Nut	Brass	Nickel Plating	1		 		PART DESCRIPTION: M16 Female Connector, Panel Mount, Solder, Rear fastened			
3	Center Pin	Copper Alloy	Gold Plating	14		UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 -120mm ± 0.30mm	Appd:	Jim.king	P/N: M16A-14SF-DN-R002		
2	Insulator	PA66 UL94-V0	Black	1	Check:			Date	Scale	Unit	Page
1	Shell	Brass	Nickel Plating	1	Draw:		Gavin	2025.03.12	Free	MM	1/1
NO	DESCRIPTION	MATERIAL	FINISH	QTY							