









1	2	3	4	5	6
REV		DESCRIPTION		DATE	APPROVEN
R1.0		First issue		2025/03/12	JIM.KING



Recommended
Panel cut-out



Technical Specifications	
Coupling	Threaded Coupling
Termination	Screw
Pollution Degree	3
Mating Cycles	≥500
IP Rating	IP67 When Mated
Temperature Range	-25°C ~ +80°C

Core count	4
Rated Voltage/Current	7A/250V
Rated Pulse Voltage	1500V
Insulation Resistance (MΩ)	≥100
Contact Resistance (mΩ)	≤5

5	Nut	Brass	Nickel Plating	1
4	Sealing Ring	NBR	Black	2
3	Center Pin	Copper Alloy	Gold Plating	4
2	Insulator	PA66 UL94-V0	Black	1
1	Shell	Brass	Nickel Plating	1
NO	DESCRIPTION	MATERIAL	FINISH	QTY

-TOLERANCES-
UNLESS OTHERWISE
SPECIFIED

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS
ARE:
0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.25mm
30 - 120mm ± 0.30mm



Metabee (Chengdu) Technology Co., Ltd.
Tel: +8615926241606 E-mail: Sales@metabeeai.com



PART DESCRIPTION: **M16 Female Connector,
Panel Mount, Solder, Rear fastened**

Appd:

Jim.king

P/N:

M16A-4SF-DN-R002

Check:

Date

Scale

Unit

Page

Draw:

Gavin

2025.03.12

Free

MM

1/1