



Core count	5
Rated Voltage/Current	6A/250V
Rated Pulse Voltage	1500V
Insulation Resistance (M Ω)	≥ 100
Contact Resistance (m Ω)	≤ 5

					-TOLERANCES- UNLESS OTHERWISE SPECIFIED	 Metabee (Chengdu) Technology Co., Ltd. Tel: +8615926241606 E-mail: Sales@metabeeai.com					
5	Nut	Brass	Nickel Plating	1		UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 -120mm ± 0.30mm			PART DESCRIPTION: M16 Female Connector, Panel Mount, Solder, Front fastened		
4	Sealing Ring	NBR	Black	2	Appd:		Jim.king	P/N: M16A-5SF-DN-F002			
3	Center Pin	Copper Alloy	Gold Plating	5	Check:			Date	Scale	Unit	Page
2	Insulator	PA66 UL94-V0	Black	1	Draw:		Gavin	2025.03.12	Free	MM	1/1
1	Shell	Brass	Nickel Plating	1							
NO	DESCRIPTION	MATERIAL	FINISH	QTY							
1		2		3		4		5		6	