







REV	DESCRIPTION	DATE	APPROVEN
R1.0	First issue	2024/03/12	JIM.KING



Pinout



4P A-CODE

Technical Specifications

Coupling	Threaded Coupling
Termination	Screw
Pollution Degree	3
Mating Cycles	≥500
IP Rating	IP67 When Mated
Temperature Range	-25°C ~ +80°C

Core count	4
Rated Voltage/Current	3A/60V
Rated Pulse Voltage	800V
Insulation Resistance (MΩ)	≥100
Contact Resistance (mΩ)	≤3

-TOLERANCES-
UNLESS OTHERWISE
SPECIFIED

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS
ARE:
0.5 ~ 8mm ± 0.20mm
8 ~ 30mm ± 0.25mm
30 ~ 120mm ± 0.30mm



Metabee (Chengdu) Technology Co., Ltd.

Tel: +8615926241606 E-mail: Sales@metabeeai.com



PART DESCRIPTION:

M8 Male Connector, injection molding

P/N:

M8-04-A-P-4-S-N

Appd:

Jim.king

Check:

Gavin

Draw:

Gavin

Date

2024.03.12

Scale

Free

Unit

MM

Page

1/1