

R/A M8 male Connector Panel Mount, PCB Type

Features:

- Threaded Coupling
- IP67 (Rating)
- Pollution Degree: 3
- Products Comply With IEC 61076-2-101 Industry 4.0 Agreement, NEMA2000 Standard



Electrical Specifications

Contacts	3	4	5	6	8
Rated Current (A)	3	3	3	1.5	1.5
Rated Voltage (AC,V)	60	60	60	30	30
Rated Pulse Voltage (AC,V)	800	800	800	800	800
Insulation Resistance (MΩ)	≥100	≥100	≥100	≥100	≥100
Contact Resistance (mΩ)	≤3	≤3	≤3	≤3	≤3

Mechanical Specifications

Mating Cycles	500 Min
Coupling Mechanism	Threaded
Interface Specification	IEC 61076-2-101


Environmental Specifications

Temperature Range	-20°C to +85°C
-------------------	----------------

Material Specifications


Shell	Brass, Nickel Plating
Shielded	Brass, Nickel Plating
Insulator	PA66 UL94-V0, Black
Contacts	Copper Alloy, Gold Plating
Sealing Ring	NBR, Black
Nut	Brass, Nickel Plating

Drawing



Recommended
Panel cut-out


PCB Layout



Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.

Part Number



UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS
ARE:

0.5 - 8mm $\pm$ 0.20mm
8 - 30mm $\pm$ 0.25mm
30 -120mm $\pm$ 0.30mm

Part Number:

M8-XX-X-P-1-R-B

Code:
A,B

Core count:
03, 04, 05, 06, 08

Disclaimer

The information in this specification is subject to change without notice. Please confirm the latest version before use. Technical parameters are for reference only, and sufficient testing and verification should be conducted in actual applications.