

MOTION CONNECT 300

MLFB-Ordering data:

6FX3002-5BL03-1CA0



Client Order no.:

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks:

Electrical data

No. of cores x cross-section mm ²	2 x 0.75
Test voltage, rms Power conductors	500 V
Rated voltage U ₀ /U in accordance with EN 50395 Power conductors	30 V/30 V

Mechanical data

Smallest bending radius (fixed installation)	6 x diameter
Smallest bending radius (flexible installation)	155mm
Number of bends, max.	1,000,000
Tensile stress, max. Fixed installation	50 N/mm ²
Tensile stress, max. Flexible installation	20 N/mm ²
Torsional stress	Absolute 30°/m
Connection type	Straight connector (fixed cable outlet direction)
Length	20.0 m

Technical data

Ambient temperature

Operation with permanently installed cable -25 to +80°C

Kind of connection cable Brake Cable

Material of the cable sheath PVC

Type of insulation PVC

Degree of protection IP65

Standard for behavior in fire: flame resistance EN 60332-1-1 to 1-3

Oil resistance EN 60811-2-1 (mineral oil only)

Verification of suitability, CE marking No

Verification of suitability, UL approval No

Verification of suitability, RoHS conformity Yes