

M12 Circular Connector

Part Number :

M12-04-A-P-4-S



Client Order no.: Item no. :
Order no. : Consignment no. :
Offer no. : Project :
Remarks :

Basic Information

Connector Series:	M12 Field Wireable Connector
Connector Gender:	Male
Orientation:	Straight
Connector Coding:	A Coded
Number of Contacts:	4 Pin

Materials and Plating

Shell Material:	Brass
Shell Plating:	Nickel-plated
Insulation Material:	Polyamide 66 GF25
Contact Material:	CuZn
Contact Plating:	Au

Electrical Performance

Rated Voltage:	250V
Rated Current:	4A
Insulation Resistance:	$\geq 100 \text{ M}\Omega$
Contact Resistance:	$< 10 \text{ m}\Omega$
Standard:	IEC 61076-2-101
Shielding Performance:	Unshielded


Mechanical Performance

Coupling method:	Threaded Coupling
Threaded Size:	M12x1
Mount Method	Cable Type
Mount Feature	Not Applicable
Contact Termination	Screw Joint
Cable Od	Not Applicable
Thread Aperture	Not Applicable
Durability	≥500 cycles
Wire Gauge	0.14/0.25/0.34/0.5mm ² /(26/24/22/20AWG)

Environmental Performance

Temperature Range:	-25°C to 85°C
Ip Rating:	IP67

M12 Connector Part Number Breakout



Learn more about this connector on [Metabee's M series connector catalog](#).

M12 Connector Pinout and Wiring Diagram

Pins	A	B	C	D	X	Y	S	T	K	L	M	
2												
3												
4												
5												
6												
8												
12												
17												

芯位 Pins	线芯颜色 Wire core color
2芯(Pins)	
1	BN
2	-
3	BU

芯位 Pins	线芯颜色 Wire core color
3芯(Pins)	
1	BN
2	-
3	BU
4	BK

芯位 Pins	线芯颜色 Wire core color							
4芯A编码(4 Pins A-Code)			4芯B编码(4 Pins B-Code)			4芯D编码(4 Pins D-Code)		
1	BN		BN		YE			
2	WH		WH		WH			
3	BU		BU		OG			
4	BK		BK		BU			

芯位 Pins	线芯颜色 Wire core color		
5芯A编码(5 Pins A-Code)		5芯B编码(5 Pins B-Code)	
1	BN	BN	
2	WH	WH	
3	BU	BU	
4	BK	BK	
5	GY	GY	

芯位 Pins	线芯颜色 Wire core color
12芯(Pins)	
1	BN
2	BU
3	WH
4	GN
5	PK
6	YE
7	BK
8	GY
9	RD
10	VT
11	OG
12	LTGN

芯位 Pins	线芯颜色 Wire core color
17芯(Pins)	
1	BN
2	BU
3	WH
4	GN
5	PK
6	YE
7	BK
8	GY
9	RD
10	VT
11	OG
12	LTGN
13	LTBU
14	BKWH
15	BNWH
16	RDWH
17	BUWH

芯位 Pins	线芯颜色 Wire core color
6芯(Pins)	
1	BN
2	WH
3	BU
4	BK
5	-
6	GY
7	RD

芯位 Pins	线芯颜色 Wire core color
8芯(Pins)	
1	WH
2	BN
3	GN
4	YE
5	GY
6	PK
7	BU
8	RD

The Ultimate Guide to M12 Connector Pinout, Color Code, and Wiring Diagram – MetabeeAI (PDF Format, 33 pages, 4.5MB)

Thanks!

Our team of passionate experts brings a wealth of experience to the table, ready to collaborate with you and unlock your full potential. By joining forces, we can create innovative solutions and achieve remarkable things.



CONTACT US

Phone: +86 159 2624 1606

E-mail: sales@metabeeai.com

Web: metabeeai.com & metabee.com

Address: Room 708, 7th Floor, Building 2, No. 489, Guanghuadong Third Road,
Qinyang District, Chengdu, Sichuan, China