


APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	01/17/13	
A		ADDED PIN SPEC.	3/27/15	AY/TW
B		UPDATE SPEC.	5/16/17	AY/MY
C		UPDATE TEMPERATURE	1/22/18	AY/AC
D		ADDED DIM.	3/5/18	AY/YC



RECOMMENDED PCB LAYOUT

Pin No.	Signal Type	Pin No.	Signal Type
1	In	11	GND
2	GND	12	In
3	In	13	CONFIG
4	In	14	CONFIG
5	GND	15	I/O
6	In	16	GND
7	In	17	I/O
8	GND	18	Out
9	In	19	RTN
10	In	20	Power Out

SPECIFICATIONS:

Material:

Insulator: Hi-temp thermoplastic, rated UL 94V-0

Insulator color: Black

Contact: Brass

Shell: Brass, Nickel plated

Plating:

Gold flash over Nickel underplate on contact area,

Tin over Nickel underplate on solder tails

Electrical:

Operating voltage: 40 VAC max

Current rating: 0.5 Ampere per contact

Contact Resistance: 30 mohms max.

Insulation Resistance: 100 Mohms min.





Withstanding Voltage: 500 VDC

Temperature Rating:

Operating temperature: -40°C to +85°C

Environmental:

Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES
.X ±.10 Ø.X ±.10
.XX ±.020 Ø.XX ±.015
.XXX ±.015 Ø.XXX ±.010

APPROVALS		DATE
DRAWN	TW	01/17/13
CHECKED	YC	01/17/13
APPROVED		



Metabee (Chengdu) Technology Co., Ltd.

Tel: +8615926241606 E-mail: Sales@metabeeai.com

TITLE
DISPLAYPORT RECEPTACLE, R/A, SMT TYPE
20 PINS, W/ PEG, W/ BOARDLOCK

SIZE	PART NO.	REV.
X	DPC-F-S-RA-SMT-P-BL	D
REF:	S00078T	SCALE: NTS
		SHEET 1 OF 1