

6

5

4

3


2

1

APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	8/25/16	



Mating with: PH1-3E-03-FHMP-6075
PH1-3E-03-FVMP-6085

SPECIFICATIONS:**Connector:**

P1 = USB Connector, A Type, Male, 10u" Gold plated,
Insulator Color: Lucency, Overmold Color: Black, PVC
P2 = Magnetic pogo pin 3P connector, Insulator Color: Lucency, Overmold Color: Black, PVC

Cable:

22AWGX2C, O.D.: 3.5mm, Jacket Color: Black, 55P PVC

Electrical Test:

All Assemblies must be 100% Tested for
Shorts, Open, Continuity, and Physical Appearance.

Environmental:

Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED
HOLES
MM
.X ± .25
.XX ± .15
.XXX ± .05

APPROVALS		DATE
DRAWN	HR	8/25/16
CHECKED	CK	8/25/19
APPROVED		



TITLE			
CUSTOM CABLE ASSEMBLY, USB A TYPE 2.0 PLUG TO MAGNETIC POGO PIN 3P CONNECTOR			
SIZE X	PART NO. CA-USBAM-PH-3E03-MVCC	REV. -	
REF: S00170C	SCALE: NTS	SHEET 1 OF 1	