




APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-	7426	RELEASED	01/11/07	
A		REDRAWN	10/5/11	
B		UPDATE DRAWING	4/11/16	AY/JK
C		UPDATED SPEC.	9/12/18	HR/LW



RECOMMENDED P.C.B. LAYOUT

SPECIFICATIONS:

Material:

Insulator: Hi-temp thermoplastic, rated UL 94V-0

Insulator color: Black

Contacts: Phosphor Bronze

Hold Down: Brass, Matte Tin plated

Plating:

Gold over Nickel underplate on contact area

Gold flash over Nickel underplate on solder tails

Electrical:

Voltage rating: 150 VAC max

Current rating: 1.5 Amps max

Contact resistance: 20 mohms max

Insulation resistance: 500 Mohms min @ 500 VDC

Dielectric withstanding voltage: 1000 VAC for 1 minute

Temperature Rating:

Operating temperature: -40°C to +85°C

Environmental:

Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MM [INCHES]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES

.X ± .10 Ø.X ± .10
.XX ± .020 Ø.XX ± .015
.XXX ± .015 Ø.XXX ± .010

APPROVALS		DATE
DRAWN	BW	01/11/07
CHECKED		
APPROVED		



TITLE
TELEPHONE JACK, SMT, TOP ENTRY,
4P4C, SURFACE MOUNT

SIZE X	PART NO. MTJ-44HX1	REV. C
REF: S00065T	SCALE: NTS	SHEET 1 OF 1