

6

5

4

3

2

1

APPROVED: _____

DATE: _____ TITLE: _____

Rev

AWO #

Description




Date

Appr



-

RELEASED

11/15/18



SECTION A-A

Magnet fixed
with glue

SPECIFICATIONS:

Material:

Insulator: HTN, rated UL 94V-0

Insulator color: Black

Contact: Pogo pin, 5u" Gold plated

Magnet: N52 NdFeB, Ni-Cu-Ni plated

Electrical:

Rating Current & Voltage rating: 12VDC, 3A

Contact resistance: 50 mohms max

Environmental:

Lead free, RoHS compliant.

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE MILLIMETERS
TOLERANCES: EXCEPT AS NOTED
ANGLEMM
0~6 ± 0.10
6~30 ± 0.20
30~150 ± 0.30

±2°

APPROVALS DATE

DRAWN

HR

11/15/18

CHECKED

AC

11/15/18

APPROVED

TITLE
2.54MM PITCH POGO PIN, FEMALE, 4P
SINGLE ROW, MAGNET, STRAIGHTSIZE
X

PART NO.

PH1-3L-04-FVMP-4560

REV.

-

REF: S00170C

SCALE: NTS

SHEET 1 OF 1

6

5

4

3

2

1