



APPROVED: _____

DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	5/10/19	
A		REDRAWN	5/22/24	JJ/TW
B		UPDATE SPEC.	10/16/24	LL1/AL



4.30mm Length



4.30mm Length
Positions: 01 thru 40 Unit:mm

ADAM P/N	Initial Height
PH2-3B-XX-MVS-4355-C1	5.5mm
PH2-3B-XX-MVS-4360-C1	6.0mm

5.30mm Length



5.30mm Length
Positions: 01 thru 40 Unit:mm

ADAM P/N	Initial Height
PH2-3B-XX-MVS-5365-C1	6.5mm
PH2-3B-XX-MVS-5370-C1	7.0mm
PH2-3B-XX-MVS-5375-C1	7.5mm
PH2-3B-XX-MVS-5380-C1	8.0mm

SPECIFICATIONS:

Material:

Insulator: PA46, rated UL 94V-0, Color: Black

Contacts: Brass

Spring: Stainless Steel

Plating:

Gold flash over Nickel underplate overall

Electrical:

Voltage rating: 12 Volts

Current rating: 3A max

Contact resistance @ working stroke: 50 mohms max Δ

Insulation resistance: 100 Mohms min

Dielectric withstanding voltage: 100 VRMS @ 60HZ

Mechanical:

Spring force: 70g $\pm$ 20g @ 1.0mm working stroke (4.30 & 5.30mm)

Full stroke: 1.40mm

Life test: 10,000 Cycles Min

Temperature Rating:

Operating temperature: -30°C to +85°C

Environmental:

Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

INCHES	HOLES
.X $\pm$.10	$\varnothing$ X $\pm$.10
.XX $\pm$.020	$\varnothing$ XX $\pm$.015
.XXX $\pm$.015	$\varnothing$ XXX $\pm$.010

DRAWN	OW	5/10/19
CHECKED	AC	5/10/19
APPROVED		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH



TITLE
CUSTOM LENGTH TUBE DOUBLE ROW STRIPS
1.50MM INSULATOR HEIGHT, SOLDER CUP

SIZE X	PART NO. PH2-3B-XX-MVS-XXXX-C1	REV. B
REF: S00185C	SCALE: NTS	SHEET 1 OF 1